PCT/GB 2004 / 0 0 2 7 2 8

INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 22 JUL 2004
WIPO PC

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed R. Mahoney

Dated 13 July 2004

BEST AVAILABLE COPY

THE PATENT OFFICE
TW
27 JUN 2003
RECEIVED BY FAX

Patents Form 1/77

Patents Act 1977
(Rule 16)

The Patent Office

1/77

27JUN03 E818333-1 C6397
P01/7700 0.00-0315009.1

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference — 03.038-lpw/ph

2. Patent application number *(The Patent Office will fill in this part)* — 0315009.1

27 JUN 2003

3. Full name, address and postcode of the or of each applicant *(underline all surnames)* — IPWireless, Inc.
1001 Bayhill Drive, 2nd Floor
San Bruno, California
CA 94066

Patents ADP number *(if you know it)* — 8169401002

If the applicant is a corporate body, give the country/state of its incorporation — USA, Delaware

4. Title of the invention — METHOD AND ARRANGEMENT FOR TCP FLOW CONTROL

5. Name of your agent *(if you have one)* — Peter Hudson

"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)* — InetIP
121 Blackberry Lane
Four Marks, Alton
Hampshire GU34 5DJ

Patents ADP number *(if you know it)* — 7987423001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number

Country	Priority application number *(if you know it)*	Date of filing *(day / month / year)*

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing *(day / month / year)*

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:*

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Yes

0073083 27 Jun 03 08:36

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	
Description	14
Claim(s)	5
Abstract	1
Drawing(s)	3

10. If you are also filing any of the following, state how many against each item.

Priority documents	
Translations of priority documents	
Statement of inventorship and right to grant of a patent *(Patents Form 7/77)*	
Request for preliminary examination and search *(Patents Form 9/77)*	
Request for substantive examination *(Patents Form 10/77)*	
Any other documents *(please specify)*	

11. I/We request the grant of a patent on the basis of this application.

Signature Peter D. Hudson Date 27 June 2003

12. Name and daytime telephone number of person to contact in the United Kingdom — Peter Hudson — 01420 562568

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

b) Write your answers in capital letters using black ink or you may type them.

c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.

d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.

e) Once you have filled in the form you must remember to sign and date it.

f) For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

METHOD AND ARRANGEMENT FOR TCP FLOW CONTROL

Field of the Invention

This invention relates to TCP (Transmission Control Protocol) flow control, and particularly (though not exclusively) to TCP flow control in wireless communication systems.

Background of the Invention

TCP is a transport protocol in the internet protocol suite (see for example, the publication by W.R. Stevens, 'TCP/IP illustrated, Volume 1: The protocols', Addison-Wesley, Reading, Massachusetts, November 1994). It is used in applications such as telnet FTP (File Transfer Protocol) and HTTP (HyperText Transfer Protocol). TCP is designed for wire networks which have very low error rates.

Flow control in TCP is governed by two windows: the sender's congestion window ('cwnd') and the receiver's advertised window ('awnd'). Flow control is based on the minimum of these 2 windows. The 'cwnd' is modified dynamically to match the capacity in the network. Most importantly it is reduced whenever packets are lost as this is an indication of congestion in the network. The 'awnd' is based on the receiver's ability to buffer data that it receives and it can be dynamically reduced if the

receiver is unable to cope with the rate of reception of data. The initial value of 'awnd' is controlled by parameters configured in the TCP protocol stack.

As mentioned above, TCP is designed for low error rate networks. Therefore any packet losses which occur in TCP are regarded as due to network congestion and are therefore followed by a reduction in 'cwnd' and consequently in the data rate of the sender as mentioned above. However, this is not appropriate to wireless networks which are inherently high error rate systems. Therefore, the 3GPP (3rd Generation Partnership Project) standard provides ARQ (Automatic Repeat Request) functionality, known as RLC (Radio Link Control - see, for example, the 3GPP technical specification 3GPP TS 25.322) that allows packets to be re-transmitted which have been subjected to error due to transmission over the air interface. However, the use of ARQ schemes result in the packets arriving out of order, so they have to be buffered before they can be passed on to TCP. The use of buffering introduces increased delay and this can result in increased RTT (Round Trip Time).

Assuming that the highest rate services are provided in the downlink, this means that large buffering is likely to be required in the network node, i.e., the RNC (Radio Network Controller) in the case of 3GPP systems. The following considers this downlink (DL) problem. However the present invention is also appropriate for controlling uplink TCP flows.

The maximum DL rate specified in the 3GPP technical specification 3GPP TS 34.108 is 2Mbps. Assuming that it is not possible to alter the TCP protocol stack at the receiver (i.e., UE), it is therefore necessary that the UE must advertise a window at least equal to the bandwidth delay product appropriate for the 2Mbps service. If the UE is to support the maximum rate of 2Mbps then the advertised window must be extremely large. If a smaller rate is then provided to the UE (due, for example, to the fact that many UE's are requesting service at the same time) then buffer overflow might occur. If buffer overflow does not occur the round trip time (RTT) will be very high since data will spend a long time buffered at the network node.

High RTT will have a negative impact on performance perceived by the user. This is particularly true in the case of the user wishing to continue web browsing while downloading a large file via FTP; the web browsing session will appear to be extremely slow. Therefore we wish to provide a flow control technique to maintain a target RTT for any rate provided by the network while maintaining the ability to download data at rates up to the maximum 2Mbps rate.

As mentioned previously, flow control is provided by the sender's 'cwnd' and the receiver's 'awnd'. Since control of the sender's 'cwnd' resides in the server, it can be located remotely and is not in any way controllable. It is therefore necessary that flow control is provided by the 'awnd'.

A number of schemes (discussed briefly below) for flow control have been suggested for TCP over 3G wireless systems. However, the issue with which these are most concerned is preventing the buffer at the network node from overflowing (i.e., the sending node in the case of data download).

In the publication by Koga, Kawahara and Oie, "TCP flow control using link layer information in mobile networks", Proceedings of SPIE Conference of Internet Performance and Control of Network Systems III, Boston, Massachusetts 7, 2002, it is proposed that the receiver, i.e., the UE in the most likely case of file download, modifies the TCP window that it advertises based not on the capacity of the receivers buffers as is conventionally the case but on measures obtained from the RLC. This approach is extremely problematic since it means modification of the TCP protocol stack at the UE and it may not be possible to obtain control of this stack. This is particularly true in the case where a PC (Personal Computer) is connected to a UE (which acts effectively as a modem) and the TCP protocol stack resides in the PC.

The publication by Seok, Joo and Kang, "A-TCP: A mechanism for improving TCP performance in wireless environments", IEEE broadband wireless summit, May 2001 suggests a scheme whereby two entirely split connections are made, one between the server and the network node and another between the network node and the UE. This requires considerable additional complexity and may not

be of any benefit for transfers using UDP (User Datagram Protocol).

The publication by Bakre and Badrinth, "I-TCP: indirect TCP for mobile hosts", Proceedings of the 15th International conference on distributed computer systems, May 1995, suggests modifying the TCP window size in TCP ACKs (ACKnowledge packets). However in this publication the goal is simply to modify the TCP window size to the available buffer size at the network node. Limiting the buffer occupancy as in this publication does not guarantee a specified RTT.

A need therefore exists for method and arrangement for TCP flow control wherein the abovementioned disadvantage(s) may be alleviated.

Statement of Invention

In accordance with the a first aspect of the present invention there is provided an arrangement for TCP flow control as claimed in claim 1.

In accordance with the a second aspect of the present invention there is provided method for TCP flow control as claimed in claim 12.

Brief Description of the Drawings

One method and arrangement for TCP flow control incorporating the present invention will now be described, by way of example only, with reference to the accompanying drawing(s), in which:

FIG. 1 shows a block schematic diagram illustrating a 3GPP radio communication system in which the present invention may be used;

FIG. 2 shows a block schematic diagram illustrating protocol architecture for U-plane showing functional location of a TCP window modification function based on the present invention; and

FIG. 3 shows a block schematic diagram illustrating steps performed in the TCP flow control method between a server and a user equipment client terminal via a radio network controller.

Description of Preferred Embodiment(s)

The following preferred embodiment of the present invention will be described in the context of a UMTS Radio Access Network (UTRAN) system operating in TDD mode. Referring firstly to FIG. 1, a typical, standard UMTS Radio Access Network (UTRAN) system 100 is conveniently considered as comprising: a terminal/user

equipment domain 110; a UMTS Terrestrial Radio Access Network domain 120; and a Core Network domain 130.

In the terminal/user equipment domain 110, terminal equipment (TE) 112 is connected to mobile equipment (ME) 114 via the wired or wireless *R* interface. The ME 114 is also connected to a user service identity module (USIM) 116; the ME 114 and the USIM 116 together are considered as a user equipment (UE) 118. The UE 118 communicates data with a Node B (base station) 122 in the radio access network domain 120 via the wireless *Uu* interface. Within the radio access network domain 120, the Node B 122 communicates with a radio network controller (RNC) 124 via the *Iub* interface. The RNC 124 communicates with other RNC's (not shown) via the *Iur* interface. The Node B 122 and the RNC 124 together form the UTRAN 126. The RNC 124 communicates with a serving GPRS service node (SGSN) 132 in the core network domain 130 via the *Iu* interface. Within the core network domain 130, the SGSN 132 communicates with a gateway GPRS support node (GGSN) 134 via the *Gn* interface; the SGSN 132 and the GGSN 134 communicate with a home location register (HLR) server 136 via the *Gr* interface and the *Gc* interface respectively. The GGSN 134 communicates with public data network 138 via the *Gi* interface.

Thus, the elements RNC 124, SGSN 132 and GGSN 134 are conventionally provided as discrete and separate units (on their own respective software/hardware platforms) divided across the radio access network domain 120 and the core network domain 130, as shown the FIG. 2.

The RNC 124 is the UTRAN element responsible for the control and allocation of resources for numerous Node B's 122; typically 50 to 100 Node B's may be controlled by one RNC. The RNC also provides reliable delivery of user traffic over the air interfaces. RNC's communicate with each other (via the Iur interface) to support handover and macrodiversity.

The SGSN 132 is the UMTS Core Network element responsible for Session Control and interface to the HLR. The SGSN keeps track of the location of an individual UE and performs security functions and access control. The SGSN is a large centralised controller for many RNCs.

The GGSN 134 is the UMTS Core Network element responsible for concentrating and tunnelling user data within the core packet network to the ultimate destination (e.g., internet service provider - ISP).

Such a UTRAN system and its operation are described more fully in the 3GPP technical specification documents 3GPP TS 25.401, 3GPP TS 23.060, and related documents, available from the 3GPP website at www.3gpp.org, and need not be described in more detail herein.

In the present example, all functionality of the invention resides in the RNC 124 but can alternatively be applied at the UE 118.

Referring now to FIG. 2, as will be explained in greater detail below, in order to improve TCP flow for download of data to a UE 118 a modification 210 of the TCP window occurs at the radio bearer level, and is functionally located in the protocol architecture for the user plane (U-plane). In the RNC 124 and Node B 122 of the UTRAN 126 TCP window modification 210 (which will be explained in greater detail below) is followed by PDCP (Packet Data Convergence) processing 220, RLC (Radio Link Control) processing 230, MAC (Medium Access Control) processing 240 and PHY (Physical Layer) processing 250. It will be understood that the PDCP processing 220, RLC processing 230, the MAC processing 240 are performed in accordance with the known 3GPP technical specifications TS 25 323, TS 25 322 and TS 25 321 respectively. PHY processing is described in 3GPP technical specifications TS 25 2xx (e.g., 221, 222, 223, 224 & 225 for TDD). In all cases there is no need to describe these in further detail herein.

The processed information is communicated across the wireless *Uu* interface to the UE 118, where complementary PHY processing 260, MAC processing 270, RLC processing 280 and PDCP processing 290 are performed. As above, it will be understood that the PDCP processing 290, RLC processing 280, the MAC processing 270, and the PHY processing 260 are performed in accordance with the known 3GPP technical specifications TS 25 323 TS 25 322 and TS 25 321 respectively. PHY processing is described in 3GPP technical specifications TS 25 2xx (e.g., 221,

222, 223, 224 & 225 for TDD). In all cases there is no need to describe these in further detail herein.

Referring now also to FIG. 3, TCP window modification 210 is based on the following steps:

- At 310, when a TCP packet (302) carrying data is received at RNC 124 from a server 140 for download to UE 118, a target buffer delay is specified and known, and a measurement of the delay within the transmit buffer of the RLC on downlink traffic is made. A TCP packet (304) carrying data is sent across the wireless *Uu* interface to the UE 118.
- At 320, in the UE 118 an 'awnd' value is calculated based on the UE receiver's buffer capacity and placed in the 'win' field in the ACK (ACKnowledge) packet (306) which is sent back to the RNC 124.
- At 332-336, in the RNC 124 a new value of 'awnd' is determined as follows:
  - o at 332, a target RLC buffer delay is subtracted from the RLC buffer delay measured at step 310,
  - o at 334, a desired control loop gain multiplier is applied, and
  - o at 336, the 'awnd' value previously determined in the RNC 124 is added.
- At 340, the next available SDU (Service Data Unit) containing a TCP ACK packet is identified. The 'win' field value in the received ACK packet is compared with the value determined at step 330. If the value determined in step 330 is less than the 'win' value in the received ACK packet then the 'win' value in

the packet is replaced with that determined in step 330. However, if the value determined in step 330 is greater than that in the received ACK packet no change is made.

- At 350, the TCP checksum is recalculated to take account of the modified TCP ACK.
- At 360, the ACK packet is reconstructed and a TCP packet (308) with modified ACK is sent to the server 140.

No more changes to the TCP window are made until all current data in the system has been ACKed (this can be measured conveniently by waiting until the number of ACKs reaches half the current number of SDUs in the system when the delayed ACK function is implemented in the TCP protocol stack).

It will be appreciated that since the RLC buffer delay parameters must be signaled through PDCP, the PDCP protocol layer could be considered a suitable location for this functionality to reside.

It will be understood that ideally it would be desirable to measure overall round trip time (RTT) for a packet and accordingly implement flow control. However, in practice measuring the RTT based on ACK and SEQ numbering can be difficult since there are typically multiple TCP streams at any one moment. The total RTT is made up of the components shown in the following equation:

RTT = sender RLC buffer delay + sender to receiver air interface delay + receiver buffer delay + receiver to sender air interface delay.

The inventors of the present invention have realised that, assuming the volume of data associated with ACKs is low compared to data sent from sender to receiver, the receiver buffer delay can be affected by flow controlling the sender. Also, the time taken over the air interface (although variable due to retransmissions, etc.) can also be regarded as not affected by flow control. Therefore, all that needs to be monitored is the time an SDU spends in the RLC transmit queue.

Also, simply measuring the time to traverse RLC transmit queue may be problematic since even when no new SDUs are added to the back of the queue the traverse time will be high for the last SDU. The following method is therefore conveniently used:

1. For each SDU in the RLC transmit queue, measure:
   a. The current buffer size at the time when the SDU enter the RLC transmit queue.
   b. The time taken from the moment an SDU enters the RLC transmit queue to the moment it leaves the transmit queue (i.e., all PDU which make up the SDU have been sent at least once).
2. Determine the mean of a predetermined number of most recent SDUs for which the buffer size and buffer delay are available.
3. If mean buffer delay is relatively close to (within a predetermined range about) target delay,

Modify TCP 'awnd' window by an amount related to (target buffer delay - mean buffer delay) * control loop gain as in steps 332-336 of FIG. 3. Note that a 'dead band', centred on desired target delay, may be applied where no adjustment is made.

4. If mean buffer delay is considerably greater than (outside a predetermined range about) target delay,

   Adjust TCP window to the amount indicated by the current mean buffer size minus a predetermined quantity.

5. When a modification to the TCP window size is made no more changes are allowed to TCP window size until this change has taken effect.

6. A minimum allowed calculated window can be configured, so that the determined TCP window size determined in stages 3 and 4 above cannot fall below this value.

It will be appreciated that the process for TCP flow control described above will typically be carried out in software running on a processor (not shown), and that the software may be provided as a computer program element carried on any suitable data carrier (not shown) such as a magnetic or optical computer disc. It will also be appreciated that the TCP flow control scheme described above may alternatively be fabricated in an integrated circuit for use in a terminal or RNC of a communication system.

It will be appreciated that although the TCP flow control scheme has been described above in the context of a downlink data transfer in a UTRA TDD system, the invention is not limited to such an application and may be used in downlink and/or uplink data transfer in communication systems generally.

It will be understood that the method and arrangement for TCP flow control described above provides the advantage that RTT (i.e., the latency of the system) can be substantially guaranteed, irrespective of the throughput that the user is allocated. In comparison, it should be noted that using target buffer occupancy - as in the above-mentioned prior art publication "I-TCP: indirect TCP for mobile hosts" - does not allow the above condition to be met because buffer occupancy varies with throughput for a given RTT.

Claims

1. An arrangement for Transmission Control Protocol (TCP) flow control in a communication system, the arrangement comprising:

means for determining delay in a transmit buffer of the system; and

means for modifying TCP window size dependent on the determined delay.

2. The arrangement of claim 1 wherein the means for modifying TCP window size comprises:

means for sending to a TCP server of the system in an acknowledge packet an indication of modified TCP window size.

3. The arrangement of claim 1 or 2 wherein the means for modifying TCP window size comprises:

means for determining a new TCP window size as a function of the determined transmit buffer delay, a target transmit buffer delay, and a previously determined TCP window size.

4. The arrangement of claim 3 wherein the function is also a function of control loop gain.

5. The arrangement of any one of claims 1-4 arranged to make, following a change in TCP window size, no further changes until receipt of a number of acknowledge packets substantially equal to half the current number data units in the system.

6. The arrangement of any one of claims 1-4 wherein the means for determining delay in a transmit buffer of the system comprises:

means for determining mean buffer delay of a plurality of data units passing through the transmit buffer and for producing the determined delay as a function of the mean buffer delay.

7. The arrangement of claim 6 arranged to modify TCP window size, if the mean buffer delay is within a predetermined range about a target delay, by an amount related to the difference between the mean buffer delay and the target delay.

8. The arrangement of claim 7 arranged to modify TCP window size, if the mean buffer delay is outside a predetermined range about a target delay, by an amount related to difference between current mean buffer size and a predetermined value.

9. The arrangement of any one of claims 1-8 comprised in a network controller of the system.

10. The arrangement of any one of claims 1-9 wherein the system comprises a radio communication system.

11. The arrangement of claim 10 wherein the radio communication system comprises a UTRAN system.

12. A method for Transmission Control Protocol (TCP) flow control in a communication system, the method comprising:

determining delay in a transmit buffer of the system; and

modifying TCP window size dependent on the determined delay.

13. The method of claim 12 wherein the step of modifying TCP window size comprises:

sending to a TCP server of the system in an acknowledge packet an indication of modified TCP window size.

14. The method of claim 12 or 13 wherein the step of modifying TCP window size comprises:

determining a new TCP window size as a function of the determined delay, a target transmit buffer delay, and a previously determined TCP window size.

15. The method of claim 14 wherein the function is also a function of control loop gain.

16. The method of any one of claims 12-15 comprising inhibiting making, following a change in TCP window size, no further changes until receipt of a number of acknowledge packets substantially equal to half the current number data units in the system.

17. The method of any one of claims 12-15 wherein the step of determining delay in a transmit buffer of the system comprises:

determining mean buffer delay of a plurality of data units passing through the transmit buffer and for producing the determined delay as a function of the mean buffer delay.

18. The method of claim 17 comprising modifying TCP window size, if the mean buffer delay is within a predetermined range about a target delay, by an amount related to the difference between the mean buffer delay and the target delay.

19. The method of claim 18 comprising modifying TCP window size, if the mean buffer delay is outside a predetermined range about a target delay, by an amount related to difference between current mean buffer size and a predetermined value.

20. The method of any one of claims 12-19 performed in a network controller of the system.

21. The method of any one of claims 12-20 wherein the system comprises a radio communication system.

22. The method of claim 21 wherein the radio communication system comprises a UTRAN system.

23. A computer program element comprising computer program means for performing substantially the method of any one of claims 12-22.

24. An integrated circuit comprising the arrangement of any one of claims 1-11.

20. A method for TCP flow control substantially as hereinbefore described with reference to the accompanying drawings.

21. An arrangement for TCP flow control substantially as hereinbefore described with reference to the accompanying drawings.

Abstract

METHOD AND ARRANGEMENT FOR TCP FLOW CONTROL

An arrangement (124) and method (310-360) for Transmission Control Protocol (TCP) flow control in a communication system, by: determining delay in a transmit buffer of the system; and modifying TCP window size dependent on the determined delay. An indication of modified TCP window size is preferably sent to a TCP server (140) of the system in an acknowledge packet (310).

The invention is particularly suitable for TCP flow control in wireless communication systems (e.g., UTRA) systems, and has the advantage that RTT (i.e., the latency of the system) can be substantially guaranteed, irrespective of the throughput that a user is allocated.

03.039-ipw



FIG. 1

100


Radio bearer
210
TCP window modification
220
PDCP
230
RLC
240
MAC
250
PHY
RNC / Node B
126
Uu
290
PDCP
280
RLC
270
MAC
260
PHY
UE
118

FIG. 2


140
Server
124
RNC
118
UE / client
TCP packet carrying data
302
310
Measure RLC tx buffer delay
TCP packet carrying data
304
320
'awnd' calculated based on receiver's buffer capacity and placed in 'win' field in ACK packet
Target RLC Buffer Delay
332
Loop gain
334
Previous RNC-determined 'awnd'
336
New value of 'awnd'
TCP ACK packet is identified and 'win' value in TCP header modified
340
TCP ACK packet
306
350
Recalculate TCP checksum
360
Reconstruct ACK packet
TCP packet with modified ACK
308

FIG. 3

PCT/GB2004/002728

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☑ FADED TEXT OR DRAWING
- ☑ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☑ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.
As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.